



형식 구분도 | Type Classification Diagram - LED Type |




Y S	P L	2	—	A L	1 1	R	W
Yong Sung	표시등 (Pilot Lamp)	취부구경 (Attach. dia.)		사용방식 (Using method)	정격전압 (Rated voltage)	LED 색상 (LED color)	방수등급 (Waterproof grade)
		2 : Ø25 3 : Ø30		AL : AC LED DL : DC LED	24 : AC/DC24V 48 : AC/DC48V 11GPT 11 : AC/DC110V 12 : AC120V/DC125V 22GPT 22 : AC/DC220V 23 : AC230V 24 : AC240V 38 : AC380V 44 : AC440V	R : 적 (Red) Y : 황 (Yellow) G : 녹 (Green) W : 백 (White) O : 오렌지 (Orange) N : 청 (Navy blue)	W : IP 56 (Ø25, Ø30) 무표시 : 일반 (No mark : general)

※ DC용은 surge 전압발생우려가 있는 곳에 사용시 사전대책이 필요합니다. (기술자료참조)
 (As use for DC can exist to surge voltage, protective action is necessary before use. (Refer to technical data,))
 ※ IP 56 방수 : 주문 생산품 (IP 56 waterproof : Ordered production.)
 ※ GPT : GPT 3차 전압용 램프 (GPT : GPT 3rd Lamp for Voltage)
 ※ 이외의 전압은 주문사양입니다. (Products with other rated voltages are order production.)




외형 / 치수도 | Shape / Dimension Drawing |

(unit : mm)




YS PL2 (Ø25)



YS PL2-O (Ø25)



YS PL3 (Ø30)



표시등